

BlueCast Unique+ Castable Resin for Jewelry 500ml

X-One® is the real meltable resin developed and produced by **BlueCast**® for DLP and Monochromatic LCD machines. Thanks to the low-temperature melting polymer it ensures a smooth surface finish and perfect lettering.

Read More

SKU: 3DWK89USPI64O-1

Price: 1,399.00 DH

Stock: instock

Categories: Casting resins, Functional Resins, Resins

Product Description

New generation castable resin for Monochromatic LCD and DLP 3D Printers! Unique + ® is the real meltable resin developed and produce by BlueCast® for DLP and Monochromatic LCD machines. Thanks to the low temperature melting polymer it ensures smooth surface finish and perfect lettering. Uni It was developed by BLueCast R&D in order to allow perfect casting results with any kind of investments and burnout cycles.

Description

BLUECAST Unique+ for mono LCD/DLP Revolutionizing new High Wax Resin, Melts at low temperatures can be cast at any casting house, Just use the same wax burnout schedule they have been using. The Advantages of this resin are Endless, one Formulation for Mono and DLP Machines, this is not recommended to be used on Poly LCD (long print times) and Formlab printers. The main Unique futures are: – Perfect casting results with any kind of investments and burnout cycles. Low temperature burnout compatibility. – Low-temperature melting polymer ensures a smooth surface finish and perfect lettering. – Extreme accuracy and exceptional detail without shrinkage. – No bleeding issue also on LCD machines. – The first real meltable resin at low temperature. – Excellent dimensional stability in time. No shrinkage (natural shrinkage will be compensated during printmaking polymer expand chemically). – Low viscosity (easier to clean, easier to get back from patterns). – Strong adhesion to the platform, no need to primer. – Toxic and carcinogenic

component free. - Low fumes emission during burnout - The first castable resin was developed for the new Generation MONO LCD and DLP printers. - Finally, you can cast in any casting house/service every kind of pattern with text, engravings, micropavè, etc. Size: 500g

BlueCast X-One Settings



3D Blend Elastic white Resin 500ml

Read More

SKU: 3DWZ5A8MHJH66

Price: 549.00 DH

Stock: instock

Categories: Engineering Resins, Functional Resins,

Resins

Tags: #dental

Product Description





BlueCast X-10 Castable Resin for Jewelry 500ml

Advanced castable 3D resin for smooth surfaces and precise details on relatively large models. BlueCast X10 allows the printing of jewellery with high metal requirements. It has properties almost identical to those of wax and can, therefore, be processed with the same toolset.

Read More

SKU: 3DW37BWD8J9NB

Price: 1,399.00 DH

Stock: instock

Categories: Casting resins, Functional Resins, Resins

Product Description

Advanced castable 3D resin for smooth surfaces and precise details on relatively large models. BlueCast X10 allows the printing of jewellery with high metal requirements. It has properties almost identical to those of wax and can, therefore, be processed with the same toolset.

Description

BLUECAST X10 SLA/DLP *Improvements from the X5* **Improved Castability Dimensional stability improved Build platform adhesion improved Suitable for all kind of jewelry** – Excellent casting of small engravings both positive and negative.

Suitable for all jewelry needs: from filigree to medals and chaton settings to signet rings. – Excellent for stones presetting (improved elasticity). – No smell. – Negligible shrinkage (0.7% after 7 days). – Easy welding with wax. – Excellent yield of details with all investments. No chemical aggression of the investment during the burnout cycle. – Possible manual finishing (post-cure is needed). – Monomers free. – Extremely detailed. – Smooth surfaces. – Burnout cycle improved. – Suitable for all fast burnout cycles. – Full burnout also at a lower temperature (740°C, flask). – Excellent dimensional stability in time. Washing mode: Ethyl / IPA alcohol 30 seconds Drying with compressed air UV care: Not needed if casting immediately, if not, cure until turns white Shrinkage: Very light Color: Light Blue Size: 500 g

At a relatively low temperature of 740 °C, complete burnout is possible. The resin only needs to be post-cured when post-processing techniques such as polishing are applied to the 3D printing part. Otherwise, a post-cure is not required. Storing a pattern for 7 days results in a negligible shrinkage of 0.7%, which is especially useful when patterns need to be prepared in advance. The resin may lose colour when exposed to UV light. It is completely normal and does not affect the specified properties. **Applications**

- Large jewellery
- Filigree jewellery
- Medals

Clean burnout During complete burnout at 740 ° C, no ashes remain. The BlueCast X10 can be used in all burnout cycles. **Smooth surfaces** Smooth surfaces and dimensional accuracy allow the printing of large models. **Negligible shrinkage** The models can be pre-printed in 3D as the resin shrinks by only 0.7% in 7 days.

Signal word: Warning

Precautionary statements:

- P273 Avoid release to the environment.
- P405 Store locked up.
- P501 Dispose of contents/container according to local/national regulations.

Hazard statements:

- H361f Suspected of damaging fertility.
- H412 Harmful to aquatic life with long lasting effects

BlueCast X10 Settings



eResin Dental Castable 1000ml

Read More

SKU: 3DWM264T8I9CP

Price: 1,299.00 DH

Stock: instock

Categories: Functional Resins, Professional Resins,

Resins

Tags: #dental, 3d, print, resin

Product Description

Short curing time No deformation during modling Smooth surface High precision. Good strength and toughness Excellent molding and resistance to impact. Baking at 200°C without craking.

Castable resin for Dental Recommended Settings For Printer:

Castable resin for Dental Recommended Settings For Printer

	Exposure Time s	Bottom Exposure	Layer Height mm	Bottom Layer	Lift [
		Time s	Lay or morgine mini	Height mm	
ELEGOO Saturn	4	40	0,05	5	7
ELEGOO Mars 2 Pro	4	40	0,05	5	5
ANYCUBIC Photon Mono X	1,8	60	0,05	6	8
ANYCUBIC Photon Mono 4K	4,5	45	0,05	6	6
ANYCUBIC Photon Mono SE	3	35	0,05	6	6
VOXELAB Proxima 8.9	3,5	40	0,05	5	8
PHROZEN Sonic Mighty 4K	4,2	40	0,05	6	8
CREALITY HALOT ONE	5	50	0,05	10	6
CREALITY LD006	2,8	45	0,05	5	7



eSUN PMMA-Like 3D Printer Rapid Resin, 405nm LCD UV-Curing Ultra Transparency Acrylic 1000ml

Read More

SKU: 3DWF6T78LIEY4

Price: 1,299.00 DH

Stock: instock

Categories: Engineering Resins, Functional Resins,

Resins

Tags: #dental, 3d, print, resin

Product Description

What is Ultra Transparency PMMA-Like Resin?

• eSUN PMMA-Like Resin solves the problem that ordinary transparent resin turns yellow after printing and irradiating ultraviolet rays, it has transparent appearance of imitating acrylic and glass, resulting in better visual effects.

Specifications of Ultra Transparency PMMA-Like Resin:

- Net Weight: 500g & 1000g (Two Capacities)
- Material: Resin Monomer & Photo Initiator
- Available Color: Transparent

Recommended Printing Parameter:

- Normal Exposure Time: <u>18-24s</u> (AnyCubic Photon, Nova Bene 1), <u>12-16s</u> (eSUN LCD 3.0, Nova Bene 4, Wanhao D7), 4-6s (eSUN LCD 13.3, Phrozen Sonic Mini 2K)
- Bottom Exposure Time: <u>≥80s</u> (AnyCubic Photon, Nova Bene 1), <u>≥60s</u> (eSUN LCD 3.0, Nova Bene 4, Wanhao D7), ≥30s (eSUN LCD 13.3, Phrozen Sonic Mini 2K)
- Number of Bottom Layers: 3-5
- Lifting Distance: <u>5-6mm</u> or More for 5.5 & 6 Inch 3D Printers; <u>8-12mm</u> or More for 8.9 & 13.3 Inch 3D Printers
- Lifting Speed (mm·min-1): 90-150 (AnyCubic Photon, Nova Bene 1), 90-120 (eSUN LCD 3.0, Nova Bene 4, Wanhao D7), 50-90 (eSUN LCD 13.3, Phrozen Sonic Mini 2K)
- Descending Speed(mm·min-1): <u>150-200</u>

eSUN PMMA-Like 3D Printer Rapid Resin, 405nm LCD UV-Curing Ultra Transparency Acrylic eSUN PMMA-Like 3D Printer Rapid Resin, 405nm LCD UV-Curing Ultra Transparency Acrylic eSUN PMMA-Like 3D Printer Rapid Resin, 405nm LCD UV-Curing Ultra Transparency Acrylic eSUN PMMA-Like 3D Printer Rapid Resin, 405nm LCD UV-Curing Ultra Transparency Acrylic

PM200 PMMA LIKE Recommended Settings for Printer:

PM200 PMMA Like Recommended Settings For Printer

	Exposure Time s	Bottom Exposure Time s	Layer Height mm	Bottom Layer Height mm
ELEGOO Saturn	6	40	0,05	5
ELEGOO Mars 2 Pro	5	40	0,05	5
ANYCUBIC Photon Mono X	2,2	30	0,05	6
ANYCUBIC Photon Mono 4K	3,5	30	0,05	6
ANYCUBIC Photon Mono SE	5	35	0,05	6

0,05 VOXELAB Proxima 8.9 6,5 40 5 40 0,05 6 PHROZEN Sonic Mighty 4K 5 **CREALITY HALOT ONE** 55 0,05 10 8,5 0,05 5 **CREALITY LD006** 4 33 5 0,05 5 ELEGOO Mars 3 40

25

0,05

4

WooCommerce PDF Catalog

7

AnyCubic Ultra